

## DOUBLE HORIZONTAL SCISSORS

Two mechanically synchronized scissor systems behind each other allow a big platform length with highest stability and maximized safety.

This design is applicable where high loads have to be lifted, where big platforms are required and where the closed height is restricted.



Type	Lifting capacity kg	Lifting height mm	Closed height mm	Length mm	Width mm	Lifting time sek.	Power kW	Weight kg
3021	1000	550	160	1800	650	16	0,37	210
3060	1000	1000	210	4000	1000	36	0,75	
3310	2000	830	180	2600	650	36	0,75	290
3311	2000	830	180	2600	800	36	0,75	310
3315	2000	1000	210	3000	800	36	0,75	460
3316	2000	1000	210	3000	1000	36	0,75	480
3320	2000	1400	250	4000	900	35	2,20	755
3321	2000	1400	250	4000	1200	35	2,20	845
3443	3000	1100	230	3400	900	44	0,75	550
3444	3000	1100	230	3400	1200	44	0,75	590
3733	3000	1650	300	5000	1200	40	2,20	1100
3512	4000	820	210	2600	800	54	0,75	440
3562	4000	1400	250	4000	900	70	2,20	920
3563	4000	1400	250	4000	1200	70	2,20	1010
3565	4000	1500	250	4400	1200	70	2,20	920
3743	6000	1100	250	3400	900	50	2,20	775
3776	6000	1600	350	5000	1300	55	3,00	2000
3820	8000	1300	300	4000	1500	108	3,00	1680
3821	8000	1300	300	4000	2000	108	3,00	1800
3862	8000	1500	350	4400	1200	108	3,00	1550