

LOW PROFILE SCISSOR LIFT

With this extra-low design the hydraulic power pack and the electric controls are located separate from the lifter.

A pit for installation is not required, due to the minimal closed-height.



Type	Lifting capacity kg	Lifting height mm	Closed height mm	Length mm	Width mm	Lifting time sek.	Power kW	Weight kg
4130	600	550	85	1200	800	12	0,75	220
4131	600	1100	105	2000	1000	24	0,75	550
4132	1000	720	85	1500	800	12	0,75	250
4133	1000	720	85	1500	1000	12	0,75	275
4135	1000	900	85	1500	800	15	0,75	230
4136	1000	900	85	1500	1000	15	0,75	255
4232	1500	720	85	1500	800	15	1,1	300
4233	1500	720	85	1500	1000	15	1,1	320
4235	1500	900	85	1500	800	19	1,1	270
4236	1500	900	85	1500	1000	19	1,1	290
4220	2000	700	100	1500	800	16	1,1	300
4222	2000	700	100	1500	1000	16	1,1	350

LOW PROFILE DESIGN, DOUBLE HORIZONTAL

4410	1200	550	85	2400	800	24	0,75	400
4420	2000	720	85	3000	800	24	0,75	455
4422	2000	720	85	3000	1000	24	0,75	505
4430	2000	900	85	3000	800	30	0,75	415
4432	2000	900	85	3000	1000	30	0,75	465
4520	3000	720	85	3000	800	30	1,1	560
4522	3000	720	85	3000	1000	30	1,1	600
4530	3000	900	85	3000	800	38	1,1	510
4532	3000	900	85	3000	1000	38	1,1	560